

WILKINS Cross Reference Guide

RELIEF VALVES

| TEMPERATURE AND PRESSURE RELIEF VALVES | | | |
|---|--------------------|-----------|-----------|
| WILKINS | WATTS | CONBRACO | CASH-ACME |
| TP220-3C | 40L-3 | N/A | FVMX-3C |
| TP220-5C | 40XL-5 | N/A | FVMX-5C |
| TP220-8C | 40XL-8 | N/A | FVMX-8C |
| TP1100A-2C | 10L-2 | 18-402 | NCLX-1 |
| TP1100A-4C | 100XL-4 | 18-402 | NCLX-5 |
| TP1100A-8C | 100XL-8 | 18-402 | NCLX-8 |
| TP1100AE-3C | L100XL-3 | | |
| TP3000-5C | 140X-6 | N/A | FVX-5L |
| TP3000-8C | 140X-9 | N/A | FVX-8L |
| PRESSURE RELIEF VALVES | | | |
| P1000A | 3L | 17-402 | FWL-2 |
| P220 | 174A | N/A | F-82 |
| P3000 | 174A | N/A | F-82 |
| 34-BVEC-80 | BRVT-80 | 78-424-RV | |
| 34-BVEC-100 | BRVT-100 | 78-414-RV | |
| 34-BVEC-125 | BRVT-125 | 78-404-RV | |
| 34-BVECC-80 | BRVS-80 | 78-324-RV | |
| 34-BVECC-100 | BRVS-100 | 78-314-RV | |
| 34-BVECC-125 | BRVS-125 | 78-304-RV | |
| P1520, P1550 | 53 | | |
| P1500 | 530 (175 psi max.) | | |
| ASME RATED PRESSURE RELIEF VALVES | | | |
| WILKINS | WATTS | CONBRACO | CASH-ACME |
| P3000BR | 374A, 174A | 10-600 | F-82 |
| P3000CI | 740 | | F-95 |
| VACUUM RELIEF VALVES | | | |
| VR-10 | N36 | 37-100 | VR-801 |